

NANLITE

P-Series	NanLite P-100 5600K AC LED Monolight	NanLite P-200 5600K AC LED Monolight
Product Weight (lb)	7.9	8.2
Product Length (in)	11.6	11.6
Product Width (in)	11.6	11.4
Product Height (in)	7.1	7.1
Color Temp (Kelvin)	5600K	5600K
CRI	95	95
TLCI	93	93
Lux @ 1m 5600K	2966	8000
Lux @ 2m 5600K	715	2200
Lux @ 3m 5600K	338	1060
Lumen Output 5600K	7000	14000
Dimming	0-100%	0-100%
Beam Angle Flood	35 Degrees (Requies CN-18X)	N/A
Beam Angle Spot	12 Degrees (Requies CN-18X)	N/A
Cooling System	Fan Less, Passive	Quiet Active Fan
Max Power Consumption	125W	230W
Power Source	AC 100V-240V	AC 100V-240V
Battery Compatibility	None AC Only	None AC Only
DMX Control	No	No
Wireless Control Type	Wireless Remote / Wifi via adapter	Wireless Remote / Wifi via adapter
Compatible Remote	NanLite RC-1 Remote Control	NanLite RC-1 Remote Control
Frequency	2.4ghz	2.4ghz
Compatible Wifi Adapter	NanLite W-2 Wifi Adapter	NanLite W-2 Wifi Adapter
Mount	Bowens S-Mount	Bowens S-Mount
Warranty	Limited 2 Year Warranty (extend to 3 years total here)	Limited 2 Year Warranty (extend to 3 years total here)